

Integra Adhesives®

SURFACE BONDER RAPID

Fast curing, High strength Seaming Adhesive,
with no sag colour matched formula

Rapid means...

Increased efficiency with quicker cure times

Staying put with no drips or mess

Higher performance with stronger joints on thin sheet

Keeping healthier with no styrene



New!

Surface Bonder Rapid adhesive is developed especially to improve production output for high volume fabrication.

The high strength, no sag formula is available in a range of colours to match almost every surface design.

SURFACE BONDER RAPID

Fast curing zero sag adhesive for seaming Quartz and Natural Stone

ADVANTAGES

Fast curing
4-8 minutes working time
10-16 minutes fixture time
Non-sag formula
No drips. No Mess
Invisible Seams
High Strength
Pre-mixed for common substrate colors

APPLICATIONS

Indoor use on Natural Stone, Quartz, and Compact Ceramic & Porcelain

- ✓ Mitred edges
- ✓ Deck seams
- ✓ Laminations
- ✓ Vertical applications

CONTACT

PHONE

+44 (0) 191 259 0033

FAX

+44 (0) 191 257 4525

EMAIL & WEB

EuropeSales@integra-adhesives.com

integra-adhesives.com/europe

Integra
Adhesives

Product Overview

High volume shops need faster products! Surface Bonder Rapid is specially developed to cure in half the time of similar products to keep your fabrication shop running at peak productivity. The non-sag formula stays right where you put it... so no drips, mess or waste, making Surface Bonder Rapid ideal for mitred edges and vertical applications. Surface Bonder Rapid is high strength and so gives better performance on thinner sheets where a stronger adhesive adds strength to the final surface installation.

Designed for Natural Stone, Quartz, Compact Ceramics and Porcelain surfaces, Surface Bonder Rapid eliminates the need for stocking multiple adhesives, so you can reduce complexity, supply costs and risk of errors or reworks.

Characteristics

Characteristic	Surface Bonder Rapid
Working Time	4-8 minutes
Fixture Time	10-16 minutes
Operating Temperature	18°C-30°C (65°F-85°F)*
Viscosity- Adhesive	20,000 – 50,000 cps
Viscosity- Activator	8,000-12,000 cps
Colour- Adhesive	Various
Colour- Activator	Colourless / Translucent
Mix Ratio	10:1
Flexural Strength- Granite	>27 / MPa (N/mm ²)
Flexural Strength- Quartz	>27 / MPa (N/mm ²)
Flexural Strength- Compact Sintered Material	>27 / MPa (N/mm ²)
Shelf Life	2 years

* Use at temperatures below 12°C (55°F) or above 32°C (90°F) may cause incomplete cure, yellowing and poor bonding strength

Colour Matching

Integra Adhesives is known throughout the industry for excellence in colour matching. Our lab combines the latest technology and extensive practical knowledge to produce unrivaled colour matches. Customers have access to a large and ever-expanding palette of colours from which to choose. For accurate colour matches on a variety of surfaces, visit www.integra-adhesives.com/color-charts/ or download the Integra App from the [Apple App Store](#) or [Google Play App Store](#) by searching Integra Adhesives.

Dispensing / Packaging

Integra Adhesives is a world leader in pre-coloured cartridge-based adhesives specially designed for the surfacing industry. Our unique cartridge-based mix and dispense system allows for efficient and consistent colour match, fast production output, and low waste. Surface Bonder Rapid is available in 250ml cartridges.

Shipping Options

Integra Adhesives products are available across North America, Europe and many other parts of world. Please visit www.integra-adhesives.com to find a distributor near you.